

# Permafrix 1120

## Floorguard

*Breathable non-woven covering*



### Product description

Blue, self-adhering polyester non-woven, lined with a breathing membrane.

### Area of application

The covering of floors, stairs and objects that need to be protected. Specially suitable for moisture-sensitive coverings such as natural stone or wood, and for wet-laid floor coverings. The moisture from the substrate can escape through the non-woven covering, but the penetration of liquids is prevented.

### Properties

- Actively breathing membrane, liquid can escape
- No penetration of water or paint from above
- Non-slip surface and self-adhering non-woven
- Protects from mechanical damage

### Technical data

Carrier	100% polyester non-woven
Surface weight	180 g/m <sup>2</sup>

### EMPA test values

WDD value (EN 12572/SOP 176.104)	1.2 litres / m <sup>2</sup> / 24 h
Waterproof	W2 according to EN13859-1

### Form of delivery

50 m rolls	
Width 100 cm	22 rolls / pallet
Colour	Non-woven: light-blue
	Membranes: white

### Application

Non-woven covering laid in strips with an overlap of approx. 5 cm. These are spliced together to form a seal using a suitable adhesive tape (e.g. duct tape). If the non-woven covering is to be used several times, it must not become soiled. Preliminary trials should be carried out on sensitive substrates.

### Remarks

The data provided corresponds to the latest state of development. There is no claim to completeness. A professional, and thereby successful application of the product is beyond our control. A guarantee can therefore only be provided for the quality of the products, but not for the application. It is the responsibility of the user to ensure the suitability of our products for his specific purpose. Preliminary trials are recommended.